PJD5122

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH BRILLIANTCOLOR™ TECHNOLOGY

Easy to use, easy to afford.

ViewSonic's PJD5122 is a great little projector that offers outstanding value and performance. This SVGA resolution projector supports high definition signals and projects 2700 lumens for clear, bright images in most lighting conditions. At only 5.1 pounds, it is light and compact, making it ideal for the mobile presenter. Texas Instruments' BrilliantColor™ technology delivers brilliant, true-color and high contrast images for viewing presentations, charts, or video. With extensive connectivity, including two RGB inputs and one RGB output, the PJD5122 is an excellent multifunctional data/video projector. Eco-mode reduces fan noise for less distraction during important presentations and even extends the lamp life up to 6000 hours*. For increased security a PIN lock feature allows youto set a password to prevent unauthorized use. The PJD5122 is perfect for tabletop, ceiling mounting or taking on the road.

VERSATILE PRESENTATIONS ANYWHERE

> BrilliantColor™ technology
Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.

> Bright in virtually any setting
Packs 2,700 ANSI lumens in just 5.1 lb, and with a high 2800:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

> Set to Present
With 8 preset picture modes, including whiteboard, blackboard and cinema it is easy to put toghter a great presentation.

> Eco-mode extends lamp life
Extend the life of your lamp up to 6000 hours* and reduce noise output.

> Off to Go feature
The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.

> 3D DLP Link Ready
Supports up to 120Hz frame rate.

MORE THAN 2,500 AWARDS

VIEWSONIC
PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic®
See the difference®

PJD5122

LIGHT, BRIGHT AND PORTABLE PROJECTOR

Optional Accessories

>Replacement lamp	RLC-055
>Universal ceiling mount kit	WMK-005
>Wireless G presentation gateway	WPG-350
>2nd & 3rd year extended warranty	PRJ-EE-05-03

Projection Distance 4:3 Screen		Screen Size 4:3 Screen	
M	feet	m	Inches
1.2	3.9	0.7~0.8	28.0~31.7
1.5	4.9	09.~1.0	35.2~40.0
1.8	5.9	1.1~1.2	42.3~48.0
2	6.6	1.2~1.3	47.4~53.7
3	9.8	1.8~2.2	70.3~79.7
5	16.4	3.3~3.4	117.6~133.3
11.3	37.1	6.4~7.6	250~300

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	SVGA 800×600 (Native) / SXGA 1280×1024 (compressed)
	Lens	1.1× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Size	30"-300" / 0.89m-3.9m (Diagonal)
	Throw Distance	3.9' - 37.1' / 1.2m - 11.3m
	Throw Ratio	1.86:1-2.04:1
	Lamp	220 watt
	Lamp Life (Normal / Eco Mode)	4000 / 6000* hours
	Brightness	2700 Lumens
	Contrast Ratio	2000:1 (typ), 3000:1 (dynamic)
	Aspect Ratio	4:3 (native) and 16:9
	Color Gamut	85 % NTSC 1931 CIE
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM, SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25pfs and 30fps)
	Frequency	Fh: 31-100 KHz, Fv: 48-120 Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac	Up to 1600×1200 @ 60Hz (may require Mac Adapter)
CONNECTOR	RGB Input	2 × 15-pin mini D-sub
	RGB Output	1 × 15-pin mini D-sub
	Component	2 × 15-in mini -D-Sub (shared with RGB)
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	1 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1×RS-232 (8 Pin Mini-Din)
AUDIO	Speaker	1×5W
	Amplifier	1×1W
POWER	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	280W (Typical) / <1W (Stand-by mode)
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source
	OSD	Display: Screen color, aspect ratio, keystone, position, phase, H. size, digital zoom Picture: Preset mode: brightest, standard (Video),daylight, ViewMatch (PC), cinema, user 1/user 2, brightness, contrast, color, tint, sharpness, BrilliantColor™, color temp., save settings Source: Quick auto search System setting (Basic): Language , projector position, auto power off, blank timer, panel key lock, timer controller, splash screen System setting (Advanced): Quick cooling, high altitude mode, DCR, active VGA out, audio settings, menu settings, closed caption, lamp settings, security setting, reset all settings Information: Current system status (source, preset mode, resolution, color system, equivalent lamp hour)
OPERATING CONDITIONS	Temperature	32°F-104°F (0°C-40°C)
	Humidity	10% - 90% (non-condensing)
	Altitude	0~6,000 ft (1,800m), operational up to 10,000 ft (3048m)
NOISE LEVEL	Normal / Eco-mode	32dB / 26dB
DIMENSIONS (W x H x D)	Physical	10.4 × 3.8 × 8.86 (in) / 264 × 96.4 × 225 (mm)
	Packaging	13.8 × 8.1 × 11.2 (in) / 350 × 205 × 285 (mm)
WEIGHT	Net	5.1 lb (2.3 kg)
REGULATIONS		CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 · SalesInfo@ViewSonic.com · ViewSonic.com

*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [14947-01B-06/10] PJD5122-1

ViewSonic® See the difference®